Data Sheet
Fujitsu PRIMERGY TX300 S6 Server

No compromise tower server

PRIMERGY TX tower servers are ideal for use in SMEs or branch offices. They increase operational efficiency by providing rock solid, record-breaking, energy efficient performance. That performance is built on 20-years of pioneering work in Green IT. As a customer, you benefit from a reduction in your organization's environmental impact and lower running costs. The reliability is proven by testing the machines through 5000 boot cycles far more than other vendors do. PRIMERGY TX servers are also easy to manage via the PRIMERGY ServerView Suite, reducing IT admin workload and costs. Plus, tower to rack conversion kits are available for most TX systems, ensuring investment protection.

PRIMERGY TX300 S6

Are you looking for business continuity, especially for your core business applications?
The new TX300 S6 offers maximum levels of availability and expandability as a result of hot plug, redundant versions. It has powerful performance features as supplied by the leading Intel® Xeon® processors 5600 series together with an 8-port SAS 2.0 controller and fast PCIe Gen2 connections. Continuity is ensured as a result of the modular RAID, redundant Dual LAN features and optional redundant hot-plug power supply and fans. The "Cool-safe™" technology in the new honeycomb design ensures optimal temperatures despite peak workloads and thus ensures long-life. Optimal performance and high energy efficiency is achieved via a highly efficient power supply (92% energy efficiency), a largely no-cable motherboard and state of the art power management features. The PRIMERGY TX300 S6 has 18 DIMM slots for memory mirroring with up to 384 GB DDR3 RAM. The PRIMERGY TX300 S6 is exactly the right platform for business-critical remote sites.

Features and Benefits

Main Features	Benefits
■ Intel® Xeon® Processor 5600 Series with up to 6 core operation (up to 12 threads per socket with Hyper Threading), 12 MB shared cache, Internal Memory Management Unit (3 channels of DDR3 memory) and Intel® Turbo Boost Optimization	■ Higher overall productivity thanks to excellent CPU performance.
■ More and faster memory (18 DIMMs up to 384 GB DDR3)	■ Innovative memory for system reliability, with maximum memory protection mechanisms, ideal for virtualization.
■ Hot-plug, redundant power supply and fan option, hot-plug SAS 2.0 or SATA hard disks, modular RAID 5/6 option, Dual Gbit/s LAN, Local Service Panel (LSP) or Local Service display (LSD) module	■ Highest availability and redundancy for your core applications.
■ Internal max. 6 (8 optional)x SAS or SATA 3.5 HDD or up to 12 (20 optional)x SAS or SATA 2.5 HDD, all hot-plug, 7 PCIe Gen2 slots (2 x8, 5 x4)	■ Highest flexibility on account of state-of-the-art I/O technologies to consolidate data and applications.
■ Unique, patented solution for maximum I/O bandwith with 7x PCIe Gen2 x8 slots (two x4 wired slots are automatically used as one x8 if the neighbouring slot is empty)	■ Maximum possible I/O bandwidth; no expensive card in an empty slot required!

Technical details

PRIMERGY TX300 S6			
Housing type	Tower	Tower	Rack
Upgrade notes	Standard fans	Redundant fans	Redundant fans
Mainboard			
Mainboard type	D 2619-N		
Chipset	Intel® 5520		
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5500 series / Intel® Xeon® processor E5600 series / Intel® Xeon® processor L5600 series / Intel® Xeon® processor X5600 series		
Processor	Intel® Xeon® processor E5503 (2C/2T, 2.00 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)		
	Intel® Xeon® processor E5603 (4C/4T, 1.60 GHz, SLC: -, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)		
	Intel® Xeon® processor E5606 (4C/4T, 2.13 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)		
	Intel® Xeon® processor E5607 (4C/4T, 2.26 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)		
	Intel® Xeon® processor E5620 (4C/8T, 2.40 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)		
	Intel® Xeon® processor E5630 (4C/8T, 2.53 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)		
	Intel® Xeon® processor E5640 (4C/8T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)		
	Intel® Xeon® processor E5645 (6C/12T, 2.40 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W)		
	Intel® Xeon® processor E5649 (6C/12T, 2.53 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W)		
	Intel® Xeon® processor L5609 (4C/4T, 1.86 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 40 W)		
	Intel® Xeon® processor L5630 (4C/8T, 2.13 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 40 W)		
	Intel® Xeon® processor L5640 (6C/12T, 2.26 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3/4/4, 6.4 GT/s, Mem bus: 1333 MHz, 60 W)		
	Intel® Xeon® processor X5647 (4C/8T, 2.93 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 130 W)		
	Intel® Xeon® processor X5650 (6C/12T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)		
	Intel® Xeon® processor X5660 (6C/12T, 2.80 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)		
	Intel® Xeon® processor X5667 (4C/8T, 3.06 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)		
	Intel® Xeon® processor X5675 (6C/12T, 3.06 GHz, SLC: -, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)		
	Intel® Xeon® processor X5677 (4C/8T, 3.46 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)		
	Intel® Xeon® processor X5687 (4C/8T, 3.60 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)		
	Intel® Xeon® processor X5690 (6C/12T, 3.46 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)		
Memory slots	18 (9 DIMMs per CPU, 3 channels with 3 slots per channel)		
Memory slot type	DIMM (DDR3)		
Memory capacity (min. - max.)	2 GB - 384 GB		

Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Hot-spare memory support Memory Mirroring support
Memory notes	max. 386 GB (12x32 GB) registered or 24 GB (12x2 GB) unbuffered; min. 2 GB registered or 2 GB unbuffered, no mix of registered and unbuffered modules possible; Memory Mirroring with identical modules in each of 2 channels (2 modules per bank), Hot-spare or Performance mode with identical modules in all three channels (3 per bank)
Memory Modules Independent Mode	2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	2 GB (1 module(s) 2 GB) DDR3 LV, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
	32 GB (1 module(s) 32 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Memory Modules Mirrored Mode	4 GB (2 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	32 GB (2 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
	64 GB (2 module(s) 32 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Memory Modules Spare or Performance Mode	6 GB (3 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	48 GB (3 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
	96 GB (3 module(s) 32 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Interfaces	
USB ports	10 x USB 2.0 (3x front, 4x rear, 2x internal for backup devices plus 1x USB stick)
Graphics (15-pin)	2 x VGA (thereof 1x front optional)
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC S2 or system or shared
Serial 2 (9-pin)	1 x serial RS-232-C
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port
Onboard or integrated Controller	
RAID controller	Integrated RAID 0/1 or RAID 5/6 controller for SAS base units (option, occupies one PCIe slot). See under Components RAID controller
SATA Controller	ICH10B, 2 x SATA channel for DVD
LAN Controller	Intel® 82575EB , 2 x 10/100/1000 Mbit/s Ethernet (I/O acceleration), PXE-Boot via LAN from PXE server, iSCSI boot (also diskless) via onboard LAN
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)
Slots	
PCI-Express 2.0 x4 (mech. x8)	5 x Full height from 4 PCIe slots each two wired x4 slots can be combined to one wired x8 slot one PCIe slot is occupied with one of two possible modular RAID controllers
PCI-Express 2.0 x8	2 x Full height , both are notched x8 slot as well for x16 cards

Slots	
Slot Notes	Two of four PCI-Express Gen2 x4 slots can be used as x8, if neighbour slot is empty. One PCIe Gen2 x4 slot is occupied with a modular RAID controller.
Drive bays	
Hard disk bay configuration	6x 3.5-inch, for SAS / SATA or 12x 2.5-inch for SAS/SATA optional
Accessible drive bays	3 x 5.25/1.6-inch
Notes accessible drives	All possible options described in relevant system configurator.
Optional hard disk bays	2 x 3.5-inch hot-plug SAS/SATA or 8x 2.5-inch hot-plug SAS in HDD box (occupies 2x 5.25-inch bays)
Operating panel	
Operating buttons	On/off switch NMI button Reset button
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Panel (LSP) ServerView Local Service Display (LSD)
BIOS	
BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Microsoft® Windows Web Server 2008 R2
	Microsoft® Windows HPC Server® 2008 R2 Suite
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Microsoft® Windows® Small Business Server 2008 Standard
	Microsoft® Microsoft® Windows® Small Business Server 2008 Premium
	Microsoft® Windows Server® 2003 Enterprise Edition
	Microsoft® Windows Server® 2003 Standard Edition
	Microsoft® Windows Server® 2003 Web Edition
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	VMware vSphere™ 4.1
	VMware vSphere™ 4.1 Embedded
	VMware vSphere™ 4.1 Installable
	VMware vSphere™ 4.0
	VMware vSphere™ 4.0 Embedded
	VMware vSphere™ 4.0 Installable
	Novell® SUSE Linux Enterprise Server 11
	Novell® SUSE Linux Enterprise Server 10
	Novell® SUSE Linux Enterprise Server 10 with XEN
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
	Red Hat® Enterprise Linux 5 with XEN
	Citrix® XenServer®
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	PDA Prefailure Detection and Anaylsis ASR&R Automatic Server Recovery and Restart ServerView Suite: SV Installation Manager SV Operation Manager SV RAID Manager SV Update Management SV Power Management SV Agents Online update packages for BIOS, firmware drivers and ServerView Agents ServerView Integration solutions for Microsoft SMS, MOM, SCOM, SCCM and Altiris Deployment Solution ServerView Deployment Manager (fully functional 30-day trial version) ServerView Integration solutions for Microsoft SMS, MOM, SCOM, SCCM and Altiris Deployment Solution ServerView Deployment Manager (fully functional 30-day trial version) ServerView Remote Management (iRMC)
Option	ServerView Integration for Tivoli TEC®, Tivoli NetView, HP NNM and HP Operations Manager iRMC S2 Advanced Pack
Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.

Dimensions / Weight			
Floor-stand (W x D x H)	286 x 745 x 466 mm		
Rack (W x D x H)	482.6 mm (Bezel) / 444 mm (Body) x 748 x 177 mm		
Mounting Depth Rack	700 mm		
Height Unit Rack	4 U		
Weight	up to 40 kg		
Weight notes	Actual weight may vary depending on configuration		
Rack integration kit	Rack integration kit as option		

Dimensions / Weight (Base unit specific)			
Floor-stand (W x D x H)	286 x 745 x 466 mm	286 x 745 x 466 mm	
Rack (W x D x H)			483 x 748 x 177 mm
Mounting Depth Rack			710 mm
Upgrade notes	Standard fans	Redundant fans	Redundant fans

Environmental	
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	Standard Fan Configuration: 36 dB(A) (idle) / 37 dB(A) (operating) Redundant Fan Configuration: 41 dB(A) (idle) / 42 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	Standard Fan Configuration: 5.4 B (idle) / 5.5 B (operating) Redundant Fan Configuration: 5.9 B (idle) / 6.0 B (operating)

Electrical values	
Power supply configuration	1x 800 W hot-plug power supply (92% efficiency) plus three 120mm standard fans or 2x 800W hot-plug power supply plus three hot-plug and redundant double fans
Max. output of single power supply	800 W (92% efficiency)
Hot-plug power supply output	800 W (92% efficiency)
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	100 V - 240 V / 9.0 A 5.0 A
Rated current in basic configuration	100 V - 240 V / 4.4 A - 1.5 A
Active power (max. configuration)	560 W
Apparent power (max. configuration)	570 VA
Heat emission	2016.0 kJ/h (1910.8 BTU/h)

The following Energy Star Familiy configuration options use less energy and reduce greenhouse gas emissions:

TX300 S6 E-StarFam1

http://ts.fujitsu.com/products/standard_servers/e_efficient.html

Compliance	
Germany	TÜV GS
Europe	CE Class A *
USA/Canada	CSAc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Japan	VCCI Class A + JIS 61000-3-2
Australia/New Zealand	C-Tick
Taiwan	CNS 13438 class A

Compliance	
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://sp.ts.fujitsu.com/sites/certificates/

Components

Storage disks
SSD SATA, 3 Gb/s, 64 GB, SLC, hot-plug, 2.5-inch, enterprise
SSD SATA, 3 Gb/s, 32 GB, SLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 400 GB, SLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 200 GB, SLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 100 GB, SLC, hot-plug, 2.5-inch, enterprise
HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 3 Gb/s, 320 GB, 5400 rpm, hot-plug, 2.5-inch, economic
HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 3.5-inch, economic
HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 3 Gb/s, 160 GB, 5400 rpm, hot-plug, 2.5-inch, economic
HDD SATA, 3 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 900 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise

Hard disk notes	Mix of 3.5-inch SAS and SATA HDD is possible but requires separate RAID sets One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software.

Backup Drives
DDS Gen5, 36 GB, 3 MB/s, half height, USB 2.0
DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
LTO2HH Ultrium, 200 GB, 24 MB/s, half height, SAS 3Gb/s
LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s
LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 3Gb/s
LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s
LTO5HH Ultrium, 1500 GB, 140 MB/s, half height, SAS 6Gb/s
RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0

Optical drives	Blu-ray Disc™ Combo Drive, (2x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	Blu-ray Disc™ Triple Writer, (4x BD-RW; 16x DVD; 40x CD), half height, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I
SCSI / SAS Controller	SCSI Ctrl. 320 MB 1ch int/ext PCIe x1
	SAS Ctrl. 6 Gb 8 ports ext. PCIe Gen2 x8
	SAS Ctrl. 3 Gb 4 ports int. / 4 ports ext. PCIe x4
RAID Controller	RAID 5/6 Ctrl., HDD SAS 6 Gb, LSI , 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI SAS2108)
	Integrated RAID 5/6 Ctrl., HDD SAS 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI SAS2108)
	Integrated RAID 0/1 Ctrl., SAS/SATA 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, no BBU support (based on LSI SAS2008)
	Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gb, 4 ports int. RAID level: 0, 1, 1E, no BBU support (based on LSI 1064e)
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 8 Gb Qlogic QLE2560 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gb Qlogic QLE2562 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 8 Gb Emulex LPe1250 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gb Emulex LPe12002 MMF LC-style
LAN Controller	Converged Network Adapter 2 x 10 Gb Emulex OCe10102
	Ethernet Ctrl. 1 x 1 Gb Intel® Gigabit CT Desktop Adapter
	Ethernet Ctrl. 1 x 1 Gb Intel® PRO/1000 PF Server Adapter
	Ethernet Ctrl. 1 x 1 Gb Intel® PRO/1000 PT Server Adapter
	Ethernet Ctrl. 2 x 10 Gb Fujitsu Eth Ctrl 2x10Gbit PCIe x8 D2755 SFP+
	Ethernet Ctrl. 2 x 1 Gb Fujitsu LAN Adapter D2735-2
	Ethernet Ctrl. 4 x 1 Gb Fujitsu Eth Ctrl 4x1Gbit PCIe x4 D2745 Cu
	InfiniBand HCA 1 x 40 Gb Mellanox
	InfiniBand HCA 2 x 40 Gb Mellanox
Rack infrastructure	Cable Arm 2U for PCR M1 S and 3rd party racks
	Rackmount kit full extraction (760mm), tool less mounting
	Cable Management for asym. 19-inch PRIMECENTER Racks

Warranty	
Standard Warranty	3 years
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY TX300 S6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX300 S6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://www.fujitsu.com/PRIMERGY

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2011-10-27 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions